

CÓDIGO	MODELO TRANSM.	Ø mm	LARG. mm	HÉL. PÁS	VAZÃO m3/min	PRESSÃO mmca	POT. HP	RPM	VOLTS (V)	DBA	KG
0000348-4	EA30TTR-NY-IP55	300	370	6	45	10	1/2	1700	220/380	74	25
0002713-8	EA30TTR-AL-IP55	300	370	6	45	10	1/2	1700	220/380	74	25
0002171-7	EA35TTR-NY-IP55	350	380	6	60	12	1/2	1700	220/380	80	30
0000108-2	EA40TTR-NY-IP55	400	460	8	80	15	3/4	1700	220/380	82	35
0002675-1	EA45TTR-NY-IP55	450	525	8	105	16	1,0	1700	220/380	84	52
0003282-4	EA45TTR-AL-IP55	450	525	8	105	16	1,0	1700	220/380	84	42
0000349-2	EA50TTR-NY-IP55	500	575	10	150	25	2,0	1700	220/380	90	42
0002604-2	EA50TTR-AL-IP55	500	575	10	150	25	2,0	1700	220/380	90	50
0000350-6	EA60TTR-NY-IP55	600	615	10	250	28	3,0	1700	220/380	94	55
0000135-1	EA70TTR-NY-IP55	700	615	10	450	30	4,0	1700	220/380	94	70
0003382-0	EA40TTR-6-NY-IP55	400	460	8	55	8	0,33	1100	220/380	71	35
0003184-4	EA45TTR-6-NY-IP55	450	525	8	75	12	0,5	1100	220/380	75	42
0003182-8	EA50TTR-6-NY-IP55	500	575	10	100	18	1,0	1100	220/380	79	50
0001951-8	EA60TTR-6-NY-IP55	600	615	10	165	20	1,5	1100	220/380	83	55
0003383-9	EA70TTR-6-NY-IP55	700	615	10	290	24	2,0	1100	220/380	86	70
0000337-9	EA30MTR-NY-IP21	300	370	6	45	10	1/2	1700	127/220	74	25
0002865-7	EA30MTR-AL-IP21	300	370	6	45	10	1/2	1700	127/220	74	25
0002180-6	EA35MTR-NY-IP21	350	380	6	60	12	1/2	1700	127/220	80	30
0000211-9	EA40MTR-NY-IP21	400	460	8	80	15	3/4	1700	127/220	82	35
0002778-2	EA40MTR-AL-IP21	400	460	8	80	15	3/4	1700	127/220	82	35
0002674-3	EA45MTR-NY-IP21	450	525	8	105	16	1,0	1700	127/220	84	42
0003281-6	EA45MTR-AL-IP21	450	525	8	105	16	1,0	1700	127/220	84	42
0000351-4	EA50MTR-NY-IP21	500	575	10	150	25	2,0	1700	127/220	90	50
0003283-2	EA60MTR-AL-IP21	600	615	10	250	28	3,0	1700	127/220	94	55
0000352-2	EA60MTR-NY-IP21	600	615	10	250	28	3,0	1700	127/220	94	55

MOD ESPECIAL / MOTOR A PROVA EXPLOSÃO / 440V / HÉLICES BAIXO RUÍDO – SOB CONSULTA

AL - ALUMÍNIO / NY - PÁS DE NYLON C/ BICO ALUMÍNIO

IPI ISENTO - SUJEITO A SUBSTIT. TRIBUTÁRIA / TABELA SUJEITA A ALTERAÇÃO S/ PRÉVIO AVISO